



NOTES:

- 1) MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
PERMISSIBLE SHAFT RUNOUT .002 T.I.R.
- 2) GASKETS THROUGHOUT
- 3) SHAFT SEAL
- 4) DIMENSION IS SPACE PROVIDED FOR A BOLT ON B5 OR B14 ADAPTER KIT FOR THE IEC 80 FRAME.

X80	14.14	8.63	5.19	ZL80	17.14	11.63	8.19
W80	13.64	8.13	4.69	YL80	16.64	11.13	7.69
V80	13.14	7.63	4.19	XL80	16.14	10.63	7.19
U80	12.64	7.13	3.69	WL80	15.64	10.13	6.69
R80	12.14	6.63	3.19	Z80	15.14	9.63	6.19
N80	11.64	6.13	2.69	Y80	14.64	9.13	5.69
FRAME	C	L	AD	FRAME	C	L	AD

				TOLERANCES UNLESS SPECIFIED		ELECTRIC MOTORS GEARMOTORS AND DRIVES		DRAWN MMG 05/05/94				
				DEC.	INCHES			CHK	APPD	JRA 05/17/94		
				.X	±.1	TITLE OUTLINE TEFC DC - IEC 80		SCALE	1=2			
02 KEYWAY: 1.30 DIM WAS 1.26, ECR 73093				IPG	07/16/01			SAD	.XXX	±.005	REF	030781
01 ADDED RABBET DIMENSION				MMG	07/31/94		.XXXX	±.0005	MAT'L.	FMF	4D17FT6A	
NO.	REVISION			BY & DATE		CHK	ANG	±1/2"	FINISH	PREV		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP	CAD FILE		031065	SIZE	DRAWING NO.	REV.
						DIST				B	031065-00	02