



DECAL- CONNECTION UNDER COVER (WHEN REQ'D)
 (1) 1/2"-14 NPT (PLUGGED)

(4) 3/8-16 UNC-2B X .56 DEEP ON A φ5.875 B.C.

SPECIAL FEATURES:

- 1) SHAFT SEALS & V-RING
- 2) DRAIN HOLES IN BOTH ENDBELLS & CONDUIT BOX
- 3) GASKETS THROUGHOUT
- 4) STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE

DASH NO.	"C"	"AD"
450	10.69	4.50
500	11.19	5.00
550	11.69	5.50
600	12.19	6.00
650	12.69	6.50
700	13.19	7.00
750	13.69	7.50

CAP. DASH	"XO"
A	4.33
B	4.78
C	5.00

MAXIMUM FACE RUNOUT .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT .002 T.I.R.



**ELECTRIC MOTORS
 GEARMOTORS
 AND DRIVES**

DRAWN	RDW 06/05/01
CHK	
APPD	DWF 06/05/01
SCALE	3=8
REF	033534
FMF	
PREV	

TITLE	OUTLINE - 56C FRAME TEFC - "C" FACE
MAT'L.	WASHGUARD
FINISH	

NO.	REVISION	BY & DATE	CHK	TOLERANCES UNLESS SPECIFIED	
				DEC.	INCHES
03	ADDED DASH NO. 700 & 750, REMOVED CAST T-BOLT HOLES IN SHAFT END ENDBELL, PER ECO 04-1701	BJB 09/24/04	.X	±.1	
02	CHANGED CAP CASE TO NEW STYLE, ADDED CAP DASH	RLW 06/17/04	.XXX	±.005	
01	REVISED OUTLINE TO CURRENT STNDS.	RDW 02/11/03	SW	.XXXX	±.0005
			ANG	±1/2°	