



(4) 3/8-16 UNC-2B X .56 DEEP ON A Ø5.875 B.C.

DECAL- CONNECTION UNDER COVER (WHEN REQ'D)
 (1) 1/2-14 NPT (PLUGGED)

SPECIAL FEATURES:

- 1) SHAFT SEALS & V-RING
- 2) DRAIN HOLES IN BOTH ENDBELLS & CONDUIT BOX
- 3) GASKETS THROUGHOUT
- 4) STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE

DASH NO.	"C"	"AD"
450	10.69	4.50
500	11.19	5.00
550	11.69	5.50
600	12.19	6.00
650	12.69	6.50
700	13.19	7.00

MAXIMUM FACE RUNOUT .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT .002 T.I.R.

TOLERANCES UNLESS SPECIFIED

DEC.	INCHES
.X	±.1
.XX	±.03
.XXX	±.005
.XXXX	±.0005
ANG	±1/2°



**ELECTRIC MOTORS
 GEARMOTORS
 AND DRIVES**

DRAWN	RDW 4/7/03
CHK	
APPD	
SCALE	3=8
REF	
FMF	
PREV	

TITLE OUTLINE - 56C FRAME
 TEFC - "C" FACE

MAT'L. WASHGUARD

FINISH

THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT

RFP	4/7/03	CAD FILE	034994
DIST			

SIZE	DRAWING NO.	REV.
A	034994	02