



DASH NO.	"C"	"AD"
850	13.13	5.25
900	13.63	5.75
950	14.13	6.25

MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT .002 T.I.R.

ALL-STAINLESS
 VITON CONDUIT BOX & COVER GASKETS
 VITON O-RINGS IN ENDBELL RABBETS & UNDER THRU BOLT HEADS
 VITON SHAFT SEAL
 BREATHER PLUGS IN CONDUIT BOX & L.E. ENDBELL
 ALL STAINLESS STEEL CONSTRUCTION

		TOLERANCES UNLESS SPECIFIED		LEESON	ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN LST 11/20/03		
		DEC.	INCHES			CHK	RW 11/21/03	
		.X	±.1	TITLE		APPD	KH 11/21/03	
		.XX	±.03	OUTLINE- 56C FRAME		SCALE	1=2	
		.XXX	±.005	TEFC- "C" FACE		REF	034950	
01	CORRECTED N.P. LOCATION PER ECR 69302	LST	1/26/04	.XXXX	±.0005	MAT'L.	STAINLESS STEEL DUCK	
NO.	REVISION	BY & DATE	CHK	ANG	±1/2"	FINISH	PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE	028569	SIZE	DRAWING NO.
				DIST			B	028569
								REV.
								01