


DASH NO.	"C"	"AD"
500	14.00	5.01
550	14.50	5.51
600	15.00	6.01
650	15.50	6.51

MAXIMUM FACE RUNOUT TO BE .004 TIR  
 MAXIMUM PILOT ECCENTRICITY .004 TIR  
 PERMISSIBLE SHAFT RUNOUT .002 TIR

**WASHGUARD FEATURES:**

- 1) SHAFT SEAL & V-RING
- 2) DRAIN HOLES IN ENDBELLS & CONDUIT BOX
- 3) STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE
- 4) GASKETS THROUGHOUT

		TOLERANCES UNLESS SPECIFIED		 <b>ELECTRIC MOTORS GEARMOTORS AND DRIVES</b>	DRAWN LST 1/14/04				
		DEC.	INCHES		CHK	RW 1/15/04			
		.X	±.1		APPD KH 1/15/04				
		.XX	±.03	TITLE	OUTLINE-56C FRAME TENV- RIGID "C"	SCALE 1=2			
01	REV'D DRAIN HOLE SCREW LOC'NS IN L.E ENDBELL TO	BJB	03/18/04	.XXX	±.005	REF			
	MATCH ENDBELL MACHINING			.XXXX	±.0005	MAT'L. WASHGUARD BRAKE MOTOR			
NO.	REVISION	BY & DATE	CHK	ANG	±1/2'	FINISH			
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE	028575	SIZE B	DRAWING NO. 028575	REV. 01
				DIST					