



(4) 3/8-16 UNC-2B X .56 DEEP ON A 5.875 DIA. B.C.

SPECIAL FEATURES:

- 1) MANUAL OVERLOAD PROTECTOR
- 2) GASKETS THROUGHOUT
- 3) FLINGER ON SHAFT

DASH NO.	"C"	"AD"
500	10.81	.93
550	11.31	1.43
600	11.81	1.93
650	12.31	2.43

DASH NO.	"XO"
A	1.54
B	2.01
C	2.25

MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT .002 T.I.R.

TOLERANCES UNLESS SPECIFIED

DEC.	INCHES
.X	±.1
.XX	±.03
.XXX	±.005
.XXXX	±.0005
ANG	±1/2°



ELECTRIC MOTORS
 GEARMOTORS
 AND DRIVES

DRAWN	LST 2/2/04
CHK	RW 2/3/04
APPD	KH 2/3/04
SCALE	3=8
REF	033641
FMF	116488
PREV	

TITLE OUTLINE- 56C FRAME
 TEFC- RIGID "C"

MAT'L. FARM DUTY

FINISH

THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT

RFP	CAD FILE	028578
DIST		

SIZE	DRAWING NO.	REV.
A	028578	01

NO.	REVISION	BY & DATE	CHK
01	CHANGED CAP CASE TO NEW STYLE	RLW 6/17/04	