

3-Wire *microfast*® Cordsets, Standard Duty

- Straight Female Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4.0 A



| Housing Style | Part Number | Cable | Features | Pinout |
|---------------|---------------|--|--|-------------------------------|
| | KB 3T-* | AWM PVC Yellow 3x22 AWG 105°C 5.2 mm OD Cable #RF50531- [†] M [†] | <i>flexlife</i> ® | |
| | KB 3T-*/S90 | AWM PUR Yellow 3x18 AWG 80°C 5.7 mm OD Cable #RF50547- [†] M [†] | <i>Cut/Abrasion Immune</i> | 1. GN 2. RD/BK 3. RD/WH |
| | KB 3T-*/S105 | AWM PVC Yellow 3x22 AWG 105°C 5.7 mm OD Cable #RF50535- [†] M [†] | <i>Braided Copper Shield</i> | |
| | KB 3T-*/S749 | AWM PVC Yellow 2x22 AWG 105°C 5.2 mm OD Cable #RF50650- [†] M [†] | <i>3-pin with 2 conductors</i> | 1. N/C 2. BK 3. WH |
| | KB 3T-*/S1507 | AWM TPE Grey 3x20 AWG 105°C 5.7 mm OD Cable #RF50940- [†] M [†] | <i>Flexlife-10, High Flex - Over 10 million cycles</i> | 1. BK 2. BN 3. BU |
| | KB 3T-*/XOR | AWM PVC Yellow 3x18 AWG 80°C 250°C short term 5.7 mm OD Cable #RF04159- [†] M [†] | <i>Weld Flash Immune, High Temp Immune</i> | 1. GN 2. RD 3. RD/WH |
| | | | | |

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "KB .."; "KBK .." indicates nylon and "KBV .." indicates 316 stainless steel.


† See Section N for *reelfast*® cable information.

3-Wire *microfast*® Cordsets, Standard Duty

- Straight Male Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4.0 A



| Housing Style | Part Number | Cable | Features | Pinout |
|---------------|---------------|--|--|-------------------------------|
| | SB 3T-* | AWM PVC Yellow 3x22 AWG 105°C 5.2 mm OD Cable #RF50531- [†] M [†] | <i>flexlife</i> ® | |
| | SB 3T-*/S90 | AWM PUR Yellow 3x18 AWG 80°C 5.7 mm OD Cable #RF50547- [†] M [†] | <i>Cut/Abrasion Immune</i> | 1. GN 2. RD/BK 3. RD/WH |
| | SB 3T-*/S105 | AWM PVC Yellow 3x22 AWG 105°C 5.7 mm OD Cable #RF50535- [†] M [†] | <i>Braided Copper Shield</i> | |
| | SB 3T-*/S749 | AWM PVC Yellow 2x22 AWG 105°C 5.2 mm OD Cable #RF50650- [†] M [†] | <i>3-pin with 2 conductors</i> | 1. N/C 2. BK 3. WH |
| | SB 3T-*/S1507 | AWM TPE Grey 3x20 AWG 105°C 5.7 mm OD Cable #RF50940- [†] M [†] | <i>Flexlife-10, High Flex - Over 10 million cycles</i> | 1. BK 2. BN 3. BU |
| | SB 3T-*/X0R | AWM PVC Yellow 3x18 AWG 80°C 250°C short term 5.7 mm OD Cable #RF04159- [†] M [†] | <i>Weld Flash Immune, High Temp Immune</i> | 1. GN 2. RD 3. RD/WH |



* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "SB .."; "SBK .." indicates nylon and "SBV .." indicates 316 stainless steel.
[†] See Section N for *reelfast*® cable information.