

3-Wire *picofast*® Cordsets, Threaded Coupling Nut

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 125 VAC/VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	PKW 3M-*	AWM PVC Yellow 3x24 AWG 105°C 4.4 mm OD Cable #RF50642- [†] M [†]	<i>flexlife</i> ®	
	PKW 3M-*/S90	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50587- [†] M [†]	<i>Cut/Abrasion Immune</i>	
	PKW 3M-*/S90/S101	AWM PUR Black 3x26 AWG 105°C 4.4 mm OD Cable #RF50723- [†] M [†]	<i>Cut/Abrasion Immune, flexlife-10, High Flex - Over 10 Million Cycles</i>	
	PKW 3M-*/S90/S618	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50601- [†] M [†]	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>	
	PKW 3M-*/S760	AWM PVC Black 3x24 AWG 4.4 mm OD Cable #RF50585- [†] M [†]	<i>flexlife</i>	
	PKW 3M-*/XOR	PVC Orange 3x24 AWG 80°C, 250° C short term 4.4 mm OD Cable #RF04449- [†] M [†]	<i>Weld Flash Immune, High Temp. Immune</i>	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

** Standard coupling material is nickel plated brass.

[†] See Section N for *reelfast*® cable information.