

## 6-Wire *picofast*® Cordsets, Snap Lock (Locking Sleeve)

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 24 VDC, 1 A



Housing Style	Part Number	Cable	Features	Pinout
<p>PKW ..Z** LOCKING SLEEVE</p>	PKW 6Z-*	AWM PVC Yellow 6x26 AWG 105°C 4.5 mm OD Cable #RF50734-*M <sup>†</sup>	<i>flexlife</i> ®	
	PKW 6Z-*/S90	AWM PUR Black 6x26 AWG 105°C 4.5 mm OD Cable #RF50735-*M <sup>†</sup>	<i>Cut/Abrasion Immune</i>	
	PKW 6Z-*/S90/S618	AWM PUR Black 6x26 AWG 105°C 4.5 mm OD Cable #RF51144-M <sup>†</sup>	<i>Cut/Abrasion Immune EMI/RFI Protection</i>	
	PKW 6Z-*/S760	AWM PVC Black 6x26 AWG 105°C 4.5 mm OD Cable #RF51083-*M <sup>†</sup>	<i>flexlife</i> ®	

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.  
 \*\* Standard coupling material is POM.."PKG..Z".  
 † See Section N for *reelfast*® cable information.