

6-Wire *picofast*® Cordsets, Threaded Coupling Nut

- Straight Male Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 24 VDC, 1 A



Housing Style	Part Number	Cable	Features	Pinout
<p>PSG ..M**</p> <p>PSGV .. M**</p>	PSG 6M-*	AWM PVC Yellow 6x26 AWG 105°C 4.5 mm OD Cable #RF50734-*M <sup>†</sup>	<i>flexlife</i> ®	<p>1. BN 2. WH 3. BU 4. BK 5. GY 6. PK</p>
	PSG 6M-*/S90	AWM PUR Black 6x26 AWG 105°C 4.5 mm OD Cable #RF50735-*M <sup>†</sup>	<i>Cut/Abrasion Immune</i>	
	PSG 6M-*/S760	AWM PVC Black 6x26 AWG 105°C 4.5 mm OD Cable #RF51083-*M <sup>†</sup>	<i>flexlife</i>	
	PSG 6M-*/S90/S618	AWM PUR Black 6x26 AWG 105°C 4.5 mm OD Cable #RF51144-*M <sup>†</sup>	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>	

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

\*\* Standard coupling material is nickel plated brass.."PSG..M"; "PSGV..M" indicates 316 stainless steel.

† See Section N for *reelfast*® cable information.