

4-Wire *eurofast*® Cordsets, Standard Plug Body

- Straight Female Connector
- NEMA 1, 3, 4, 6P and IEC IP 68 Protection
- 250 VAC/300 VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	RK 4.41T-*	AWM PVC NAMUR Blue 4x22 AWG 105°C 5.2 mm OD Cable #RF50598-*M†	<i>flexlife</i> ®	
	RK 4.41T-*/S529	AWM PUR/Heavy Braid Double Jacket Yellow 4x20 AWG 105°C 5.8 mm OD Cable #RF50526-*M†	<i>Cut/Abrasion Immune</i> <i>Braided Mechanical Shield</i>	
	RK 4.43T-*	AWM PVC Yellow 4x22 AWG 105°C 5.2 mm OD Cable #RF50530-*M†	<i>flexlife</i>	
	RK 4.43T-*/S90	AWM PUR Yellow 4x22 AWG 105°C 5.2 mm OD Cable #RF50613-*M†	<i>Cut/Abrasion Immune</i>	
	RK 4.4T-*	AWM PVC Grey 4x22 AWG 105°C 5.2 mm OD Cable #RF50516-*M†	<i>flexlife</i>	
	RK 4.4T-*/S90	AWM PUR Grey 4x22 AWG 105°C, 5.2 mm OD Cable #RF50532-*M†	<i>Cut/Abrasion Immune</i>	
	RK 4.4T-*/S101	AWM TPE Grey 4x22 AWG 105°C, 5.7 mm OD Cable #RF50941-*M†	<i>flexLife-10, High Flex</i> <i>Over 10 Million Cycles</i>	
	RK 4.4T-*/S824	PLTC PVC Grey 4x22 AWG 105°C, 5.2 mm OD Cable #RF50698-*M†	<i>Tray Rated</i>	
	RK 4.4T-*/S618	AWM PVC Grey 4x22 AWG Foil/Drain 105°C, 5.2 mm OD Cable #RF50577-*M†	<i>RFI/EMI Shielding</i>	
RK 4.4T-*/S618/S824	PLTC PVC Grey 4x22 AWG Foil/Drain 105°C, 5.2 mm OD Cable #RF50773-*M†	<i>RFI/EMI Shielding</i> <i>Tray Rated</i>		

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.  
 \*\* Standard coupling nut material is nickel plated brass "RK .."; "RKK .." indicates nylon and "RKV .." indicates 316 stainless steel.  
 † See Section N for *reelfast*® cable information.