


6-Wire *minifast*® Cordsets, Standard

- Straight Female Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 300 V, 9 A



Housing Style	Part Number	Cable	Features	Pinout
	RKM 60-*M/S90/S853	AWM PUR Yellow 3x18 AWG 105°C 7.3 mm OD Cable #RF50545-*M [†]	6-pin style connector with 3 conductor	1. BN 2. N/C 3. GN/YE 4. N/C 5. BU 6. N/C
	RKM 61-*M	AWM PVC Yellow 6x18 AWG 105°C 7.3 mm OD Cable #RF50575-*M [†]	flexlife®	1. GN 2. WH 3. BU 4. Gy 5. YE 6. BN
	RKM 61-*M/S739	ITC PLTC PVC Yellow 7x18 AWG 105°C 7.3 mm OD Cable #RF50637-*M [†]	Shielded cable with drain wire, not connected at plug.	
	RKM 61-*M/S763	AWM PVC Black 6x18 AWG 105°C 7.3 mm OD Cable #RF50551-*M [†]	Shielded cable with drain wire, not connected at plug	

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass "RKM .."; "RK .." indicates nylon and "RKV .." indicates 316 stainless steel.
[†] See Section N for *reelfast*® cable information.