

4-Wire *eurofast*® Cordsets, Standard Plug Body

- Right Angle Female Connector
- NEMA 1, 3, 4, 6P and IEC IP 68 Protection
- 250 VAC/300 VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	WK 4.41T-*	AWM PVC NAMUR Blue 4x22 AWG 105°C 5.2 mm OD Cable #RF50598- [†] M [†]	<i>flexlife</i> ®	
	WK 4.41T-*/S529	AWM PUR/Heavy Braid Double Jacket Yellow 4x20 AWG 105°C 5.8 mm OD Cable #RF50526- [†] M [†]	<i>Cut/Abrasion Immune Braided Mechanical Shield</i>	
	WK 4.43T-*	AWM PVC Yellow 4x22 AWG 105°C 5.2 mm OD Cable #RF50530- [†] M [†]	<i>flexlife</i>	
	WK 4.43T-*/S90	AWM PUR Yellow 4x22 AWG 105°C 5.2 mm OD Cable #RF50613- [†] M [†]	<i>Cut/Abrasion Immune</i>	
	WK 4.4T-*	AWM PVC Grey 4x22 AWG 105°C, 5.2 mm OD Cable #RF50516- [†] M [†]	<i>flexlife</i>	
	WK 4.4T-*/S90	AWM PUR Grey 4x22 AWG 105°C, 5.2 mm OD Cable #RF50532- [†] M [†]	<i>Cut/Abrasion Immune</i>	
	WK 4.4T-*/S101	AWM TPE Grey 4x22 AWG 105°C, 5.7 mm OD Cable #RF50941- [†] M [†]	<i>flexLife-10, High Flex Over 10 Million Cycles</i>	
	WK 4.4T-*/S824	PLTC PVC Grey 4x22 AWG 105°C, 5.2 mm OD Cable #RF50698- [†] M [†]	<i>Tray Rated</i>	
	WK 4.4T-*/S618	AWM PVC Grey 4x22 AWG Foil/Drain 105°C, 5.2 mm OD Cable #RF50577- [†] M [†]	<i>RFI/EMI Shielding</i>	
	WK 4.4T-*/S618/S824	PLTC PVC Grey 4x22 AWG Foil/Drain 105°C, 5.2 mm OD Cable #RF50773- [†] M [†]	<i>RFI/EMI Shielding Tray Cable Rated</i>	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "WK .."; "WKK .." indicates nylon and "WKV .." indicates 316 stainless steel.
[†] See Section N for *reelfast*® cable information.