

2-Wire eurofast® Cordsets, Standard Plug Body

- Right Angle Male Connector
- NEMA 1, 3, 4, 6P and IEC IP 68 Protection
- 250 VAC/300 VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout
<p>WS ..**</p>	WS 4.2T-*	AWM PVC Grey 2x20 AWG 105°C 5.2 mm OD Cable #RF50529-*M <sup>†</sup>	flexlife®	
	WS 4.2T-*/S90	AWM PUR Grey 2x20 AWG 105°C 5.2 mm OD Cable #RF50772-*M <sup>†</sup>	Cut/Abrasion Immune	
	WS 4.2T-*/S748	AWM PVC Yellow 2x22 AWG 105°C 5.2 mm OD Cable #RF50650-*M <sup>†</sup>		
<p>WSK ..**</p>	WS 4.21T-*/S1511	AWM PVC Grey 2x20 AWM PVC 105°C 5.2 mm OD Cable #RF50529-*M <sup>†</sup>	flexlife	
	WS 4.21T-*	AWM PVC NAMUR Blue 2x20 AWG 105°C 5.2 mm OD Cable #RF20003-*M <sup>†</sup>		
	WS 4.21T-*/S90	AWM PUR NAMUR Blue 2x20 AWG 105°C 5.2 mm OD Cable #RF50657-*M <sup>†</sup>	Cut/Abrasion Immune	
<p>WSV ..**</p>	WS 4.22T-*	AWM PVC Grey 2x20 AWG 105°C 5.2 mm OD Cable #RF50529-*M <sup>†</sup>	flexlife	
	WS 4.23T-*			

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.  
 \*\* Standard coupling nut material is nickel plated brass "WS .."; "WSK .." indicates nylon and "WSV .." indicates 316 stainless steel.  
 † See Section N for reelfast® cable information.