

5-Wire *eurofast*® Cordsets, Standard Plug Body

- Right Angle Male Connector
- NEMA 1, 3, 4, 6P and IEC IP 68 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout	
<p><b>WS ..**</b></p> <p><b>WSK ..**</b></p> <p><b>WSV ..**</b></p>	WS 4.5T-*	AWM PVC Grey 5x22 AWG 105°C 5.7 mm OD Cable #RF50543- <sup>†</sup> M <sup>†</sup>	<i>flexlife</i> ®		
	WS 4.5T-*/S90	AWM PUR Grey 5x22 AWG 105°C 5.7 mm OD Cable #RF50649- <sup>†</sup> M <sup>†</sup>	<i>Cut/Abrasion Immune</i>		
	WS 4.5T-*/S101	AWM TPE Grey 5x22 AWG 105°C 5.7 mm OD Cable #RF50909- <sup>†</sup> M <sup>†</sup>	<i>flexLife-10, High Flex Over 10 Million Cycles</i>		
	WS 4.5T-*/S618	AWM PVC Grey 5x22 AWG Foil/Drain 105°C 5.7 mm OD Cable #RF50609- <sup>†</sup> M <sup>†</sup>	<i>RFI/EMI Shielding</i>		
	WS 4.5T-*/S715	AWM PVC Yellow 5x22 AWG 105°C 5.7 mm OD Cable #RF50684- <sup>†</sup> M <sup>†</sup>	<i>flexlife</i>		
	WS 4.5T-*/S653	AWM PVC Grey 4x22 AWG Foil/Drain 105°C 5.2 mm OD Cable #RF50577- <sup>†</sup> M <sup>†</sup>	<i>RFI/EMI Shielding</i>		1. BN 2. WH 3. BU 4. BK 5. Drain
	WS 4.5T-*/S1554	AWM PVC Black 4x22 AWG Foil/Drain 105°C 5.2 mm OD Cable #RF50794- <sup>†</sup> M <sup>†</sup>			1. BN 2. WH 3. BU 4. BK 5. GY

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass "WS .."; "WSK .." indicates nylon and "WSV .." indicates 316 stainless steel.

† See Section N for *reelfast*® cable information.